

# Package: fwlplot (via r-universe)

March 12, 2025

**Title** Scatter Plot After Residualizing Using 'fixest' Package

**Version** 0.3.0

**Description** Creates a scatter plot after residualizing using a set of covariates. The residuals are calculated using the 'fixest' package which allows very fast estimation that scales. Details of the (Yule-)Frisch-Waugh-Lovell theorem is given in Basu (2023) <[doi:10.48550/arXiv.2307.00369](https://doi.org/10.48550/arXiv.2307.00369)>.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.1

**Imports** data.table, fixest, tinyplot

**Suggests** ggplot2

**NeedsCompilation** no

**Author** Kyle Butts [aut, cre] (<<https://orcid.org/0000-0002-9048-8059>>)

**Maintainer** Kyle Butts <[kbutts@uark.edu](mailto:kbutts@uark.edu)>

**Date/Publication** 2024-06-24 13:30:02 UTC

**Repository** <https://kylebutts.r-universe.dev>

**RemoteUrl** <https://github.com/cran/fwlplot>

**RemoteRef** HEAD

**RemoteSha** 74d08938ec6806a5752066157945750e4fba153f

## Contents

fml_breaker . . . . .	2
fwl_plot . . . . .	2
get_fml_parts . . . . .	3

<b>Index</b>	<b>4</b>
--------------	----------

---

fml_breaker	<i>Break apart formula (from right to left) based on a symbole (~ or  )</i>
-------------	---

---

**Description**

Break apart formula (from right to left) based on a symbole (~ or |)

**Usage**

```
fml_breaker(fml, op)
```

**Arguments**

fml	Formula following fixest syntax.
op	String. Either ~ or

**Value**

list of symbol or language from right to left that are split at each occurrence of op.

---

fwl_plot	<i>FWL Plot</i>
----------	-----------------

---

**Description**

This function creates a bivariate plot of y and x after residualizing over a set of covariates w.

**Usage**

```
fwl_plot(fml, data, ggplot = FALSE, n_sample = 1000, alpha = 0.5, ...)
```

```
fwlplot(fml, data, ggplot = FALSE, n_sample = 1000, alpha = 0.5, ...)
```

**Arguments**

fml	Of the form $y \sim x + covs \mid fes$ following the fixest formula syntax. The x variable you want plotted should come first.
data	A dataframe object that contains the variables in fml.
ggplot	Boolean. Default is to use base R plot but if TRUE, use ggplot.
n_sample	Numeric. Number of observations to sample for each facet.
alpha	Numeric. Alpha transparency of each individual point. If NULL, will plot all rows.
...	Additional arguments passed to <code>fixest::feols</code> .

**Value**

Either NULL if ggplot = FALSE or a ggplot object if ggplot = TRUE. In either case, plots the figure.

**Examples**

```
fwl_plot(mpg ~ hp + wt | cyl, mtcars)
```

---

<code>get_fml_parts</code>	<i>Split formula into terms</i>
----------------------------	---------------------------------

---

**Description**

Split formula into terms

**Usage**

```
get_fml_parts(formula, parts_as_formula = FALSE)
```

**Arguments**

<code>formula</code>	Full formula following fixest syntax: $y \sim W \mid W\_FE \mid T \sim Z \mid Z\_FE$ .
<code>parts_as_formula</code>	Logical. If TRUE, then each part will be a right-hand side formula. Default is FALSE

**Value**

List of expressions/formula for each part of the formula. It will be of type symbol/language unless `parts_as_formula = TRUE`. Can be used with `fixest::xpd` and the dot bracket syntax to create formula. Any missing elements will be given a value of NULL. The list contains the following:

<code>y_fml</code>	The LHS
<code>w_lin</code>	The linear part of the exogenous variables
<code>w_fe</code>	The fixed effects part of the exogenous variables
<code>t_fml</code>	The endogenous variable
<code>z_lin</code>	The linear part of the instruments
<code>z_fe</code>	The fixed effects part of the instruments

# Index

`fml_breaker`, 2

`fwl_plot`, 2

`fwlplot (fwl_plot)`, 2

`get_fml_parts`, 3